# **GM – Compressor Sealing Washers**

Section 1 - HOSE BLOCKS INSERTS				
Column A	Compressor	Column B		Column C
Hose Block Side View	Suction Port Size	Suction Seal Washer 5/8" 3/4"		Discharge Seal Washer 5/8"
	5/8"	С		E/S
1. Flat Face Hose Block with 4mm Pilots	3/4"	В		E/S
	5/8"	C/S		E/ L
2. Flat Face Hose Block with No Pilots	3/4"	B/S		
	5/8"	D		F
3. Raised Face Hose Block with 7mm Pilots	3/4"	В	Α	E or F
	5/8"	D		D
4. Step Hose Block with 7mm Pilots	3/4"		Α	D
	5/8"	G		G
5. Step Hose Block with Tube Pilot	3/4"			

Section 2 - PILOT INSERTS				
	FOUR SEASONS Part No.: 24359			
S	Large Diameter: 16.0 mm (.63 in) Overall Length; 7.1 mm (.28 in)			
Small	Small Diameter: 12.9 mm (.51 in)			
	FOUR SEASONS Part No.: 24360			
L	Large Diameter: 16.0 mm (.63 in) Overall Length: 11.4mm (.45 in)			
Large	Small Diameter: 12.9 mm (.51 in)			



### NOTE:

- Compare the side view of the hose manifold to the diagrams in Section 1 Column A.
- Select the diagram that matches the hose manifold.
- Determine the size of the pilot holes (SUCTION and DISCHARGE) on the manifold hose assembly. The Size of the pilot holes will be either 5/8" or 3/4".
- The letter indicating the correct sealing washer is listed with the correct pilot insert letter size.
- 5) The sealing washer diagram is Section 3.
- Using the diameter of the pilot, determine the correct SUCTION sealing washer and pilot insert (Column B).
- Using the diameter of the pilot holes, determine the correct DISCHARGE sealing washer and pilot insert (Column C).
- 8) Remove the proper insert and washer from the kit.
- 9) DO NOT lubricate washers; install dry.
- 10) Install the sealing washer and pilot insert (if needed) onto the manifold block fitting.
- 11) Inserts must be fully seated, and sealing washers must be bottomed out against the block surface.
- 12) Install manifold block to compressor. A small space between manifold and compressor is normal. Torque Bolt to 25 ft/lbs.

## **IMPORTANT:**

All sealing surfaces must be lint and dirt free.

Refer to chart on next page for washer kit information

#### **Section 3 - Sealing Washers** FOUR SEASONS Part No.: 24354 **Edge Color:** Metal Thickness: 1.3mm (.05 in) **Outside Diameter:** 31.5mm (1.24 in) **Inside Diameter:** 17.5mm (.69 in) FOUR SEASONS Part No.: 24358 **Edge Color:** Yellow Thickness: 3.0mm (.12 in) **Outside Diameter:** 33.2mm (1.31 in) **Inside Diameter:** 15.5mm (.61 in) **FOUR SEASONS Part No.: 24353 Edge Color:** Black Thickness: 3.0mm (.12 in) **Outside Diameter:** 27.9mm (1.10 in) 15.5mm (.61 in) **Inside Diameter: FOUR SEASONS Part No.: 24355 Edge Color:** Metal 1.2mm (.05 in) Thickness: **Outside Diameter:** 27.9mm (1.10 in) **Inside Diameter:** 15.5mm (.61 in) FOUR SEASONS Part No.: 24357 **Edge Color:** Green Thickness: 5.5mm (.22 in) **Outside Diameter:** 29.9mm (1.18 in) **Inside Diameter:** 15.5mm (.61in) **FOUR SEASONS Part No.: 24356 Edge Color:** Thickness: 3.8mm (.15 in) **Outside Diameter:** 29.9mm (1.18 in) 15.5mm (.61 in) **Inside Diameter:** FOUR SEASONS Kit Part No.: N/S **Edge Color:** Metal 1.2mm (.05 in) Thickness: **Outside Diameter:** 23.6mm (.93 in) **Inside Diameter:** 15.5mm (.61in)